

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 197 835 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
17.04.2002 Bulletin 2002/16

(51) Int Cl.7: G06F 3/023, G06F 3/033,
H01H 13/70

(21) Application number: 01307090.9

(22) Date of filing: 20.08.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Blck, Andrew Raymond**
Camberley, Surrey GU15 3BY (GB)

(74) Representative: **Read, Matthew Charles et al**
Venner Shipley & Co.
20 Little Britain
London EC1A 7DH (GB)

(30) Priority: 03.10.2000 GB 0024204

(71) Applicant: **Nokia Corporation**
02150 Espoo (FI)

(54) User interface device

(57) A keypad (7) of a mobile telephone handset comprises a keymat (17) beneath which are disposed capacitive sensing plates (20, 21). The keypad may be

used in a conventional manner to enter alphanumeric data by pressing keys (18) or as a touch pad by sliding a finger over the surface of the keymat (17).




Figure 3

Description

[0001] The present invention relates to a user interface device particularly but not exclusively for a mobile telephone handset or digital communicator handset.

[0002] Portable electronic apparatus are increasingly able to support powerful software applications requiring sophisticated user interfaces. For example, laptop computers, mobile telephone handsets, personal digital assistants (PDAs) and digital communicator handsets can run browser software which enables a user to navigate content on a web page by selecting hypertext links.

[0003] Conventional mobile telephone handsets have an alphanumeric keypad comprising a set of dual-state keys arranged in a grid pattern. Although the keypad is appropriate for entering text and numbers, it is not particularly suited to navigating a web page because movement of a pointer or cursor is restricted to discrete steps and is constrained to orthogonal directions defined by the grid pattern.

[0004] The present invention seeks to provide an improved user interface.

[0005] According to the present invention, there is provided a user interface device for electronic apparatus, the device comprising a keypad having a plurality of keys each arranged to actuate a respective switch so as to provide a first type of user input and integrally disposed impedance sensing means so as to provide a second type of user input.

[0006] The keypad may include a region provided with said impedance sensing means but without a key. The keys may be comprised in a keymat and the impedance sensing means may be disposed beneath the keymat. The keymat and the impedance sensing means may be coextensive. The keys may comprise silicone rubber and may include a hard coat.

[0007] The impedance sensing means may be arranged to detect the presence of a digit and may comprise first and second sensing plates.

[0008] The first sensing plate may comprise a first set of electrodes, arranged in non-contiguous stripes. The electrodes may be transparent and made from indium-tin-oxide. The first sensing plate may comprise a substrate, which is transparent and made from polyethylene terephthalate.

[0009] The second sensing plate may comprise a second set of electrodes. The first and second set of electrodes are spaced apart. A first member of the first set of electrodes and a first member of the second set of electrodes may be arranged to have a mutual capacitance and configured so to allow the mutual impedance to change when a digit touches the keypad.

[0010] The impedance sensing means may be a capacitive sensing means.

[0011] The device may further comprise a light source to illuminate the keypad, disposed behind the keys and may be planar. The light source is an electroluminescent layer.

[0012] The first type of user input may be input of alphanumeric data and the second type of user input may be control of a focus on a display of the electronic apparatus.

5 [0013] According to the present invention there is also provided an electronic apparatus incorporating a user interface device comprising a keypad having a plurality of keys each arranged to actuate a respective switch so as to provide a first type of user input and integrally disposed impedance sensing means so as to provide a second type of user input.

10 [0014] The electronic apparatus may be portable and may be a mobile telephone, communicator handset or personal computer.

15 [0015] According to the present invention there is also provided a method of fabricating a user interface device for electronic apparatus, the method comprising providing a keypad having a plurality of keys each arranged to actuate a respective switch so as to provide a first type of user input and integrally disposing impedance sensing means so as to provide a second type of user input.

20 [0016] An embodiment of the present invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a mobile telephone handset;

Figure 2 is a schematic diagram of mobile telephone circuitry;

Figure 3 is an exploded perspective view of an embodiment of the present invention;

Figure 4 is cross-sectional view taken along the line A-A' as shown in Figure 3;

Figure 5 is a plan view of the embodiment shown in Figure 3 and

Figure 6 shows a pointer displayed on a screen of the mobile telephone handset.

40 [0017] Referring to Figures 1 and 2, a mobile telephone handset 1 comprises a case 2, a battery 3, a liquid crystal display (LCD) panel 4, a microphone 5, ear piece 6, a keypad 7 having a key interface 8 and a capacitive sensing means interface 9, an antenna 10, subscriber identification module (SIM) card 11 and SIM card reader 12. The mobile telephone circuitry includes radio interface circuitry 13, codec circuitry 14, controller 15 and memory 16. Individual circuits and elements are of a type well-known in the art, for example a Nokia range in mobile telephones.

45 [0018] Referring to Figures 1, 3, 4 and 5, cutaway portions 7', 2' of the keypad 7 and case 2 are shown. The keypad 7 comprises a silicone rubber keymat 17 having a plurality of keys 18. Letters and numerals are laser-etched into the surface of the keys 18 and the keys 18 are provided with a hard protective coat (not shown). A capacitive sensing means 19 lies beneath the keymat 17 and comprises first and second sensing plates 20,

21. The first sensing plate 20 comprises a first set of striped indium-tin-oxide (ITO) electrodes 22 mounted on a first polyethylene terephthalate (PET) substrate 23. Similarly, the second sensing plate 21 comprises a second set of striped ITO electrodes 24 mounted on a second PET substrate 25. The first and second sets of electrodes 22, 24 run in orthogonal directions. For example, the first set of electrodes 22 are arranged to run parallel to the x-axis, while the second set of electrodes 24 run parallel to the y-axis. The first and second sensing plates 20, 21 are bonded together by means of a first optical adhesive layer 26. A second optical adhesive layer 27 is used to bond the sensing means 19 to the keymat 17. A third optical adhesive layer 28 is used to bond an electroluminescent back light layer 29 to the underside of the sensing means 19. When powered, the electroluminescent layer 29 illuminates the letters and numerals etched into the keys 18. The electroluminescent layer 29 is mounted to a dome adhesive gasket 30 which is adhered to a flexible substrate 31 on which metal dome switches 32 are mounted. Each dome 32 lies beneath a respective key 18, for example as shown in Figures 4 and 5. First and second metal contacts 33a, 33b are mounted on the substrate 31 beneath each dome 32. The second contact 33b is concentric with the first contact 33a. Each dome 32 sits upon a respective second metal contact 33b having the greater radius of the two contacts 33a, 33b. Respective nodules 34 on the underside of the dome adhesive gasket are used to help increase the so-called "snap ratio force" of the domes 32 when force is applied to the keys 18. Thus, this provides better tactile feel when the keys 18 are pressed.

[0019] The keypad 7 may operate as a conventional keypad and, either independently or simultaneously, as a touch sensitive pointing device.

[0020] As a conventional keypad, a user depresses a "hash" key 18a and force is transmitted through underlying layers 20, 21, 26, 27, 28, 29, 30 to deform a first key dome 32a lying underneath. Deformation of the first key dome 32a completes electrical connection between the first and second contacts 33a, 33b. This causes a signal to be generated and processed by the key interface 8 and the controller 15 in a well-known manner. This may result in the screen 4 displaying a "#" symbol. In this example, the key interface 8 generates signals which are passed to the controller 15 which runs suitable keypad driver software.

[0021] As a touch-sensitive pointing device, a user lightly touches the keymat 17 without exerting enough force to depress any of the keys 18. Beneath the user's finger lies an intersection 35 of a first electrode 22a of the first sensing plate 20 and a second electrode 24a of the second sensing plate 21. The user's finger modifies the mutual capacitance between the first and second electrodes 22a, 24a, which is detected by sensing means interface 9 in a well-known manner so as to determine the coordinate of the user's finger, which is fed

to the controller 15. The controller runs suitable touch-pad driver software. The user slides their finger over the surface of the keymat 17 and uses it as if it were a conventional touch pad. This is particularly useful when navigating a cursor 36 around a web page 37 displayed on the display 4 in order to select a hypertext link 38 as shown in Figure 6. Hypertext link 38 may be selected by lightly double tapping on the surface of the keymat 17. In this example, the whole area of the keymat 17 serves as a touch pad and not simply the keys 18. There are regions of the keymat 17, for example between the keys 18, where the user is not able to press a key but is able to control the cursor using capacitive sensing means pointing device. It will be appreciated that the user need not touch the keypad 7 to change the mutual capacitance between the electrodes. For example, the change in mutual capacitance may be sufficient enough to be detected if the user holds their finger less than a millimetre above the surface of the keypad 7.

[0022] It will be appreciated that many modifications may be made to the embodiment hereinbefore described. For example, a resistive sensing means, such as those used in resistive touch sensitive screens, may be used instead of a capacitive sensing means. The sensing means substrate may be made from other suitable plastics materials such as acrylic or polythene. The electrodes may be made from other conductive materials such as conductive polymers or thin metallic films. The keys need not be proud of the keypad. The keypad may be integrated into the case of the handset. A portion of the area of the keymat may serve as a touch pad.

[0023] It will be appreciated that the invention can be used in relation to any sort of electronic apparatus, be it portable and non-portable. This may include mobile telephone handsets and laptop computers. It may also be used in a remote control unit for electronic apparatus such as television sets, multimedia set-top boxes and audio equipment.

Claims

1. A user interface device for electronic apparatus, the device comprising a keypad (7) having a plurality of keys (18) each arranged to actuate a respective switch (32, 33) so as to provide a first type of user input and integrally disposed impedance sensing means (19) so as to provide a second type of user input.
2. A device according to claim 1, wherein the keypad includes a region provided with said impedance sensing means but without a key.
3. A device according to claim any preceding claim, wherein said keys are comprised in a keymat (17).
4. A device according to claim 3, wherein the imped-

ance sensing means is disposed adjacently to the keymat.

5. A device according to claim 3 or 4, wherein the keymat and the impedance sensing means are coextensive. 5
6. A device according to any preceding claim, wherein the keys comprise silicone rubber. 10
7. A device according to any preceding claim, wherein the keys include a hard coat.
8. A device according to any preceding claim, wherein the impedance sensing means is arranged to detect the presence of a digit. 15
9. A device according to any preceding claim, wherein the impedance sensing means (19) comprises first and second sensing plates (20, 21). 20
10. A device according to claim 9, wherein the first sensing plate (20) comprises a first set of electrodes (22). 25
11. A device according to claim 10, wherein the electrodes are arranged in non-contiguous stripes.
12. A device according to claim 10 or 11, wherein the electrodes are transparent. 30
13. A device according to claim 10, 11 or 12, wherein the electrodes are made from indium-tin-oxide.
14. A device according to any one of claims 9 to 13, wherein the first sensing plate (20) comprises a substrate (23). 35
15. A device according to claim 14, wherein the substrate is substantially transparent. 40
16. A device according to claim 14 or 15, wherein the substrate (23) is made from polyethylene terephthalate.
17. A device according to any one of claims 10 to 16, wherein the second sensing plate (21) comprises a second set of electrodes (24).
18. A device according to claim 17, wherein the first and second set of electrodes (22, 24) are spaced apart. 50
19. A device according to claim 18, wherein a first member of the first set of electrodes and a first member of the second set of electrodes are arranged to have a mutual capacitance. 55
20. A device according to claim 19, wherein said mem-

bers are arranged so to allow the mutual capacitance to change when a digit touches the keypad.

21. A device according to any preceding claim, wherein the impedance sensing means is a capacitive sensing means.
22. A device according to any preceding claim, further comprising a light source (29) to illuminate the keypad.
23. A device according to claim 22, wherein the light source is disposed behind the keys.
24. A device according to claim 22 or 23, wherein the light source is planar.
25. A device according to any one of claims 22 to 24, wherein the light source is an electroluminescent layer.
26. A device according to any preceding claim wherein the first type of user input is input of alphanumeric data.
27. A device according to any preceding claim wherein the second type of user input is control of a focus on a display of the electronic apparatus.
28. Electronic apparatus incorporating a device according to any preceding claim.
29. Electronic apparatus according to claim 28, which is portable.
30. A mobile telephone handset incorporating a device according to any one of claims 1 to 27.
31. An electronic communicator handset incorporating a device according to any one of claims 1 to 27.
32. A portable computer incorporating a device according to any one of claims 1 to 27.
33. A method of fabricating a user interface device for electronic apparatus comprising providing a keypad (7) having a plurality of keys (18) each arranged to actuate a respective switch (32, 33) so as to provide a first type of user input and integrally disposing impedance sensing means (19) so as to provide a second type of user input.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5





Figure 6



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 197 835 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
05.02.2003 Bulletin 2003/06

(43) Date of publication A2:
17.04.2002 Bulletin 2002/16

(21) Application number: 01307090.9

(22) Date of filing: 20.08.2001

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 03.10.2000 GB 0024204

(71) Applicant: **Nokia Corporation**
02150 Espoo (FI)

(72) Inventor: **Bick, Andrew Raymond**
Camberley, Surrey GU15 3BY (GB)

(74) Representative: **Read, Matthew Charles et al**
Venner Shipley & Co.
20 Little Britain
London EC1A 7DH (GB)

(54) **User interface device**

(57) A keypad (7) of a mobile telephone handset comprises a keymat (17) beneath which are disposed capacitive sensing plates (20, 21). The keypad may be

used in a conventional manner to enter alphanumeric data by pressing keys (18) or as a touch pad by sliding a finger over the surface of the keymat (17).




Figure 3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 7090

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 98 05025 A (PHILIPP HARALD ;AIRPOINT CORP (US)) 5 February 1998 (1998-02-05) * page 5, line 32 - page 6, line 8 * * page 8, line 30 - line 33; claim 3; figures 1,2 *	1-33	G06F3/023 G06F3/033 H01H13/70 G06F3/02 G06F1/16 G06K11/18
A	US 5 675 361 A (SANTILLI DONALD S) 7 October 1997 (1997-10-07) * claim 1; figure 2A *	1-33	
A	DE 42 22 940 A (DYNA SYSTEMS GMBH) 13 January 1994 (1994-01-13) * claim 1; figures 1,2 *	1-33	
A	US 5 988 902 A (HOLEHAN STEVEN D) 23 November 1999 (1999-11-23) * claim 1; figures 2,3,5 *	1-33	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G06F
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 13 December 2002	Examiner Kirsten, K
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons @ : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02.2002) (FOMC01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 7090

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-12-2002

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 9805025	A	05-02-1998	WO	9805025 A1	05-02-1998
			US	6288707 B1	11-09-2001
US 5675361	A	07-10-1997	-----		
			NONE		
DE 4222940	A	13-01-1994	DE	4222940 A1	13-01-1994
US 5988902	A	23-11-1999	US	5887995 A	30-03-1999

EPO FORM P0453

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82